

LA-UR-17-31406

Approved for public release; distribution is unlimited.

Title: Quantum Computing

Author(s): Pakin, Scott D.

Intended for: Web

Issued: 2017-12-20

Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer, is operated by the Los Alamos National Security, LLC for the National Nuclear Security Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By approving this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.

Quantum Computing

By Scott Pakin

A *bit* can be

true or **false**

left or **right** **up** or **down**

1 or **0**

set or **reset**

on or **off**

high or **low**

It is the most primitive
yes or **no**

unit of information
in or **out**

N bits can represent
any one of 2^N values


➡ 000	➡ 100
001	101
010	110
011	111

There are **four** possible
1-bit operators

- a
- \perp
- T
- $\neg a$

There are **sixteen** possible
2-bit operators

- \perp
- $a \downarrow b$
- $a \nleftarrow b$
- $\neg a$
- $a \nrightarrow b$
- $\neg b$
- $a \vee b$
- $a \uparrow b$
- $a \wedge b$
- $a \leftrightarrow b$
- b
- $a \rightarrow b$
- a
- $a \leftarrow b$
- $a \vee b$
- T



You take the blue pill, the story ends; you wake up in your bed and believe whatever you want to believe. You take the red pill, you stay in Wonderland, and I show you how deep the rabbit hole goes.

A *qubit* is a point in a
2-D Hilbert space

(i.e., a pair of complex numbers)

$$\begin{pmatrix} 1 \\ \frac{1}{\sqrt{2}} \\ 1 \\ -\frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} 1 \\ 0 \end{pmatrix} \begin{pmatrix} 0 \\ 1 \end{pmatrix} \begin{pmatrix} 0 \\ -1 \end{pmatrix} \begin{pmatrix} i - \frac{3}{2} \\ -\frac{\sqrt{12i - 1}}{2} \end{pmatrix}$$

A qubit's state as a linear combination of basis vectors:

How much
"0-ness"


$$\begin{pmatrix} 1 \\ 0 \end{pmatrix}$$

$$|0\rangle$$

How much
"1-ness"



$$\begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

$$|1\rangle$$

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

$$\alpha, \beta \in \mathbb{C}$$
$$|\alpha|^2 + |\beta|^2 = 1$$

A qubit can simultaneously have properties of both 0 and 1




We call $|\psi\rangle$ a *superposition* of 0 and 1

$$|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$$

There are an infinite number of 0s and 1s

Easier to discern from the *Bloch sphere*, a commonly used projective vector space

All $e^{i\phi}|0\rangle$ represent different *phases* of 0



N qubits can represent
all 2^N values
simultaneously

➡ 000	➡ 100
➡ 001	➡ 101
➡ 010	➡ 110
➡ 011	➡ 111

N qubits are represented with a
vector of length 2^N

Measuring
a qubit
collapses
it to a
classical
0 or 1

$\alpha|0\rangle + \beta|1\rangle$ is
measured as 0
with probability
 $|\alpha|^2$ and 1 with
probability $|\beta|^2$



Oracle: I'd ask you to sit down, but, you're not going to anyway. And don't worry about the vase.

Neo: What vase?

[Crash]

Oracle: That vase.


...

Neo: How did you know?

Oracle: Ohh, what's really going to bake your noodle later on is, would you still have broken it if I hadn't said anything?

A 2-qubit state can be constructed from the tensor product of two 1-qubit states

(and similarly for N -qubit states)

$$|10\rangle = |1\rangle \otimes |0\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix} \otimes \begin{pmatrix} 1 \\ 0 \end{pmatrix} = \begin{pmatrix} 0 \cdot 1 \\ 0 \cdot 0 \\ 1 \cdot 1 \\ 1 \cdot 0 \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ 1 \\ 0 \end{pmatrix}$$


The diagram illustrates the mapping of the 4 components of the 2-qubit state vector to the basis states. The vector components are 0, 0, 1, and 0. These are connected by lines to four green boxes on the right, labeled 00-ness, 01-ness, 10-ness, and 11-ness respectively. The 10-ness box is highlighted in yellow.

Component	Basis State
0	00-ness
0	01-ness
1	10-ness
0	11-ness

Qubits do not necessarily
have their own identity

$\left(\frac{1}{2} \quad \frac{1}{2} \quad \frac{1}{2} \quad \frac{1}{2}\right)^T$ is read as 00, 01, 10,
or 11 with 25% probability apiece

$\left(0 \quad \frac{1}{\sqrt{2}} \quad \frac{1}{\sqrt{2}} \quad 0\right)^T$ is read as 01 or 10
with 50% probability apiece

Measuring/modifying one
qubit affects the other

We call this
entanglement


There are **infinitely many** 1-qubit operators

(2×2 unitary matrices)


 reversible

- Example #1: $NOT = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$
- Example #2: $\sqrt{NOT} = \frac{1}{2} \begin{pmatrix} 1+i & 1-i \\ 1-i & 1+i \end{pmatrix}$


Visualizing some 1-qubit operators ("gates")




Pauli x gate (X)



Pauli y gate (Y)



Pauli z gate (Z)



Hadamard gate (H)

- A Hadamard gate puts a qubit in a perfect superposition of 0 and 1
- $XX = YY = ZZ = HH = I$
- Implication: deterministic \rightarrow random \rightarrow deterministic

There are **infinitely many** 2-qubit operators
(4×4 unitary matrices)

- Example #3:

$$SWAP = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

- ~~Not possible to switch 2 qubits again~~
- ~~Useful for entangling gates~~
- What if b is in a superposition?
- What if a is in a superposition?



I know what you're thinking, 'cause right now I'm thinking the same thing. Actually, I've been thinking it ever since I got here: Why, oh why, didn't I take the **blue** pill?

Quantum circuits

Quirk: 2 wires, 7 ops, HX•XMe x

algassert.com/quirk#circuit=[["cols":["H","X"],["·","X"],["Measure","Measure"],["Sample2"]]]

Menu Export Clear ALL Undo Redo Make Gate Version 2.0

Toolbox

Probes	Displays	Half Turns	Quarter Turns	Eighth Turns	Sixteenths	Spinning	Parametrized	Silly
	Sample	Z Swap	$Z^{1/2}$ $Z^{-1/2}$	$Z^{1/4}$ $Z^{-1/4}$	$Z^{1/8}$ $Z^{-1/8}$	Z^t Z^{-t}	$Z^{A/2^n}$ $Z^{-A/2^n}$	0 ?
$ 0\rangle\langle 0 $ $ 1\rangle\langle 1 $	Density Bloch	Y	$Y^{1/2}$ $Y^{-1/2}$	$Y^{1/4}$ $Y^{-1/4}$	$Y^{1/8}$ $Y^{-1/8}$	Y^t Y^{-t}	$Y^{A/2^n}$ $Y^{-A/2^n}$	-I
$ 0\rangle$ $ 1\rangle$	Chance Amps	X H	$X^{1/2}$ $X^{-1/2}$	$X^{1/4}$ $X^{-1/4}$	$X^{1/8}$ $X^{-1/8}$	X^t X^{-t}	$X^{A/2^n}$ $X^{-A/2^n}$...

Local wire states (Chance/Bloch)


Final amplitudes (assuming measurement deferred)

Toolbox₂

X/Y Probes	Order	Fourier	Inputs	Arithmetic	Compare	Modular	Custom Gates
\ominus \oplus	$+ t $ $- t $	QFT QFT [†]	input A input A[:::-1]	+1 -1	$\oplus A < B$ $\oplus A > B$	+1 mod R -1 mod R	
\otimes \otimes	Reverse		input B input B[:::-1]	+A -A	$\oplus A \leq B$ $\oplus A \geq B$	+A mod R -A mod R	
$ -\rangle\langle - $ $ +\rangle\langle + $		$e^{i\pi\%}$ $e^{-i\pi\%}$	input R R=# default	+AB -AB	$\oplus A = B$ $\oplus A \neq B$	$\times A$ mod R $\times A^{-1}$ mod R	
$ /\rangle\langle / $ $ X\rangle\langle X $			A=# default B=# default	$\times A$ $\times A^{-1}$		$\times B^A$ mod R $\times B^{-A}$ mod R	

What's the big deal?

- First answered by Deutsch and Josza in 1992



- Determine if a given black-box function is constant or balanced
 - For one bit, constant functions are $f(x)=0$ and $f(x)=1$; balanced are $f(x)=x$ and $f(x)=\neg x$
 - *Classical*: Evaluate $f(x)$ twice
 - *Quantum*: Evaluate $f(x)$ once—returns 0 for balanced, 1 for constant
- Increasing performance improvement with scale
 - *Classical*: Evaluate $f(x)$ $\lfloor N/2 + 1 \rfloor$ times for N bits
 - *Quantum*: Evaluate $f(x)$ once for N bits

Quantum algorithms

- Begin and end classically
(i.e., only $|0\rangle$ and $|1\rangle$ states)
- Quantum in between
- Can compute on all 2^N combinations
in parallel
- The catch: Only one N -bit answer
comes out

Challenges

- Reduce/cancel out probability amplitudes of non-solutions
- Manage rotations in an N -dimensional Hilbert space
- To date, only a small number of algorithms exist

Speedup over classical	#
Exponential	2
Superpolynomial	27
Polynomial	25
Constant	2
Varies	4
<i>Total</i>	<i>60</i>

Stephen Jordan
Quantum Algorithm Zoo
<http://math.nist.gov/quantum/zoo>

Unordered search




- Which screen's image matches a given pattern?
- Classical: $O(N)$ queries
- Quantum: $O(\sqrt{N})$ queries (next two slides)

Grover's search algorithm

- Given
 - A power-of-2 number of elements
 - A guarantee that exactly one element matches the pattern
 - An operator U_ω that, given an element $|x\rangle$, flips the probability amplitude iff the element matches (i.e., $U_\omega|x\rangle = -|x\rangle$ for $x = \omega$ and $U_\omega|x\rangle = |x\rangle$ for $x \neq \omega$)
- Return the matching element

Grover's search algorithm

- **Approach:** For \sqrt{N} iterations, alternately apply U_ω followed by "Grover diffusion operator" U_s
- $U_s \equiv 2|s\rangle\langle s| - I$, which flips amplitudes around the mean




Integer factorization

- Factor an integer into a product of two primes
- Best known classical algorithm has running time $O(2^{\sqrt[3]{N}})$
- Best known quantum algorithm has running time $O(\log^3 N)$ (next slide)
- Exponential speedup
- Expected that factoring a 50–100 bit number would be intractable classically but tractable with quantum: “quantum advantage”


Shor's algorithm

- It's not too hard to factor N into primes p and q if we know the period of the sequence $\{a^1 \bmod N, a^2 \bmod N, a^3 \bmod N, \dots\}$ for some $a < N$ with $p \nmid a$ and $q \nmid a$
- Apply an inverse quantum Fourier transform to find the period
- All else is classical—and randomized



Conclusions

- *Very* different form of computing
- Qubits carry more information than classical bits (e.g., phase)
- Quantum gates perform state transformations in high-D spaces
- Exploit superpositioning and entanglement for full parallelism
- Manipulate probability amplitudes to isolate correct answers
- Potential for *exponential* performance improvement



I'm trying to free your mind, Neo. But I can only show you the door. You're the one that has to walk through it.